

# SAFETY DATA SHEET

Product name: Crystal Clear Stone Seal, 951, 951F, 960, 908, 903

Issue Date: 04/25/2018

Print Date: 04/25/2018

---

## 1. IDENTIFICATION

---

Product name: Crystal Clear Stone Seal, 951, 951F, 960, 908, 903

Recommended use of the chemical and restrictions on use

Identified uses: Coatings product

### COMPANY IDENTIFICATION

The Chargar Corporation

299 Welton Street

Hamden, CT 06517

Customer Information Number:

### EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 922 4623

Local Emergency Contact: 203562-9948

---

## 2. HAZARDS IDENTIFICATION

---

### Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Flammable liquids - Category 3

Reproductive toxicity - Category 2

Specific target organ toxicity - repeated exposure - Category 1 - Inhalation

Aspiration hazard - Category 1

### Label elements

#### Hazard pictograms



Signal word: **DANGER!**

### Hazards

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Suspected of damaging fertility or the unborn child.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

**Precautionary statements****Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves/ eye protection/ face protection.  
Use personal protective equipment as required.

**Response**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage**

Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Chemical nature:** Acrylic polymer solvent based

This product is a mixture.

Component	CASRN	Concentration
Acrylic polymer(s)	Not hazardous	>= 12.0 - 30.0 %
Individual residual monomers	Not Required	<= 9,500.0 PPM
Mineral Spirits	8052-41-3	>= 70.0 - 88.0 %

---

**4. FIRST AID MEASURES**

---

**Description of first aid measures**

**Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped. In case of shortness of breath, give oxygen. Consult a physician.

**Skin contact:** Remove contaminated clothing. Wash off with soap and plenty of water. If symptoms persist, call a physician. Do not take clothing home to be laundered.

**Eye contact:** Rinse with plenty of water. If eye irritation persists, consult a specialist.

**Ingestion:** Do NOT induce vomiting. Drink 1 or 2 glasses of water. IMMEDIATELY see a physician. If vomiting occurs spontaneously, keep airway clear. Never give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** Product contains a petroleum distillate that may cause CNS symptoms.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Unsuitable extinguishing media:** no data available

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** no data available

**Unusual Fire and Explosion Hazards:** Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may be generated during combustion or decomposition.

**Advice for firefighters**

**Fire Fighting Procedures:** EXPLOSION HAZARD. Fight advanced fires from a protected location. Cool closed containers exposed to fire with water spray. Remain upwind. Avoid breathing smoke.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions, protective equipment and emergency procedures:** Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

**Environmental precautions:** WARNING: KEEP SPILLS AND CLEANING RUNOFFS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

**Methods and materials for containment and cleaning up:** Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery; use care to avoid falling. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. No sparking tools should be used. Avoid breathing vapor. NOTE: Spills on porous surfaces can contaminate groundwater.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Vapors can be evolved when material is heated during processing operations. See SECTION 8, Exposure Controls/Personal Protection, for types of ventilation required. Use non-sparking tools and grounding cables when transferring. Wash after handling and shower at end of work period. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all MSDS and label warnings even after container is emptied.

**Conditions for safe storage:** Avoid temperature extremes during storage; ambient temperature preferred. Store away from excessive heat (e.g. steampipes, radiators), from sources of ignition and from reactive materials. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Store out of direct sunlight in a cool place. Keep containers tightly closed in a cool, well-ventilated place. Avoid all ignition sources. Ground all metal containers during storage and handling.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Mineral Spirits	Rohm and Haas	TWA	100 ppm
	Rohm and Haas	STEL	200 ppm
	ACGIH	TWA	100 ppm
	OSHA Z-1	TWA	2,900 mg/m <sup>3</sup> 500 ppm
	OSHA P0	TWA	525 mg/m <sup>3</sup> 100 ppm

### Exposure controls

**Engineering controls:** Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### Individual protection measures

**Eye/face protection:** Chemical resistant goggles must be worn. Eye protection worn must be compatible with respiratory protection system employed.

#### Skin protection

**Hand protection:** Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Nitrile rubber. Butyl-rubber. Solvent-resistant gloves. Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water.

**Other protection:** Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact. Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

**Respiratory protection:** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Up to 10 times the exposure limit: Wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Up to 1000 ppm organic vapor: Wear a properly fitted NIOSH approved (or equivalent) full-facepiece, air-purifying respirator, OR full-facepiece, airline respirator in the pressure demand mode.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	
Physical state	liquid
Color	colourless clear
Odor	Sweet odor
Odor Threshold	no data available
pH	no data available
Melting point/range	no data available
Freezing point	no data available
Boiling point (760 mmHg)	158.00 °C ( 316.40 °F) Initial
Flash point	<b>Pensky-Martens closed cup</b> 37 °C ( 99 °F)
Evaporation Rate (Butyl Acetate = 1)	<1.00
Flammability (solid, gas)	Not Applicable
Lower explosion limit	0.90 % vol estimated
Upper explosion limit	6.00 % vol estimated
Vapor Pressure	1.0000000 mmHg at 20.00 °C (68.00 °F) estimated
Relative Vapor Density (air = 1)	>1.0000
Relative Density (water = 1)	0.8900
Water solubility	practically insoluble
Partition coefficient: n-octanol/water	no data available
Auto-ignition temperature	no data available
Decomposition temperature	no data available
Dynamic Viscosity	800 - 1,600 mPa.s
Kinematic Viscosity	no data available
Explosive properties	no data available
Oxidizing properties	no data available
Liquid Density	0.88 g/cm <sup>3</sup>
Molecular weight	no data available
Percent volatility	54.00 - 56.00 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** no data available

**Chemical stability:** no data available

**Possibility of hazardous reactions:** This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, open flame, heated surfaces).  
Product will not undergo polymerization.

**Conditions to avoid:** no data available

**Incompatible materials:** Avoid contact with the following: Strong oxidizing agents Strong acids and strong bases

**Hazardous decomposition products:** There are no known hazardous decomposition products for this material.

---

## **11. TOXICOLOGICAL INFORMATION**

---

*Toxicological information on this product or its components appear in this section when such data is available.*

### **Acute toxicity**

#### **Acute oral toxicity**

LD50, Rat, > 5,000 mg/kg

#### **Acute dermal toxicity**

LD50, Rabbit, > 3,000 mg/kg

#### **Acute inhalation toxicity**

Product test data not available.

### **Skin corrosion/irritation**

slight irritation

### **Serious eye damage/eye irritation**

slight irritation

### **Sensitization**

Product test data not available.

### **Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available.

### **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Product test data not available.

### **Carcinogenicity**

Product test data not available.

### **Teratogenicity**

Product test data not available.

### **Reproductive toxicity**

Product test data not available.

### **Mutagenicity**

Product test data not available.

### **Aspiration Hazard**

Product test data not available.

### **COMPONENTS INFLUENCING TOXICOLOGY:**

**Acrylic polymer(s)****Acute inhalation toxicity**

The LC50 has not been determined.

**Mineral Spirits****Acute inhalation toxicity**

Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat). May cause central nervous system effects.

LC50, Rat, vapour, > 14 mg/l

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In humans, effects have been reported on the following organs:

Bone Marrow

Liver

In animals, effects have been reported on the following organs:

central nervous system damage

Kidney.

Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

**Carcinogenicity**

No specific, relevant data available for assessment.

**Teratogenicity**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

For similar material(s): In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

**Bioaccumulative potential****Acrylic polymer(s)**

**Bioaccumulation:** No relevant data found.

**Mineral Spirits****Mobility in soil****Mineral Spirits**

Potential for mobility in soil is low (Koc between 500 and 2000).

**Partition coefficient(Koc):** 1700 Estimated.

---

**13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

(See 40 CFR 268)

**Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**14. TRANSPORT INFORMATION**

---

<b>DOT</b>	<b>Proper shipping name</b>	Resin solution
	<b>UN number</b>	UN 1866
	<b>Class</b>	3
	<b>Packing group</b>	III

**Classification for SEA transport (IMO-IMDG):**

<b>Proper shipping name</b>	RESIN SOLUTION
<b>UN number</b>	UN 1866
<b>Class</b>	3
<b>Packing group</b>	III
<b>Marine pollutant</b>	Mineral spirits
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

<b>Proper shipping name</b>	Resin solution
<b>UN number</b>	UN 1866
<b>Class</b>	3
<b>Packing group</b>	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.



---

## 15. REGULATORY INFORMATION

---

### OSHA Hazard Communication Standard

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard  
Fire Hazard

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

### Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

### California (Proposition 65)

This product contains a component or components known to the state of California to cause birth defects or other reproductive harm:

#### Components

#### CASRN

Ethylbenzene

100-41-4

### California (Proposition 65)

This product contains trace levels of a component or components known to the state of California to cause cancer:

#### Components

#### CASRN

Naphthalene

91-20-3

### United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

## 16. OTHER INFORMATION

### Hazard Rating System

#### HMIS

Health	Flammability	Physical Hazard
1	3	0